







△ P.C.B LAYOUT
Top view



△ N = Number of poles

DimL=N×5.00+1.5
DimB=(N-1)×5.00

POLES	Dim L	Dim B
1p	±0.1	
2p-6p	±0.2	±0.15
7p-12p	±0.3	±0.25
13p-18p	±0.4	±0.35
19p-24p	±0.45	±0.4

SIGN	DATE	DESCRIPTION	APPROVER
△	1/31'07	The soldering temperature from 245° to 250°	Aaron
△	05/28'13	change the structure	Da cheng
△	05/28'13	update the drawing	Da cheng
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ① Insulator body: Thermoplastic (UL94V-0)
- Item ② Insulating cover :Thermoplastic (UL94V-0)
- Item ③ Contact pin : Brass.Tin plated
- Item ④ Wire guard: Stainless steel

Electrical: cULus

- Voltage rating: 250V
- Current rating: 8A
- Wire range:
- Solid wire(AWG): 12-28
- Stranded wire(AWG): 12-28
- △ ● Wire strip length: 8-9mm
- Withstanding Voltage: 1.5KV
- △ ● Operating temperature: -40°C to +115°C
- △ △ ● Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- △ ● Critical dimension: ▽

HM xx 70 x 0 xxxx G

No. OF POLES
01: 1 POLES
02: 2 POLES
:
24: 24 POLES

△ COLOR

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7004/P)
- 9 White(RAL1102)
- C Multiple colors

0000 Standard @ Logo
000A Standard ANY Logo
Any special item by
customer request,
please contact sales
department.

△ RoHs compliant
(lead<4%)
In copper Alloy

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	HM 5.0mm Series Dip solder														
PART NO.	HMxx70x0xxxxG			DWG NO.	8HM0001										
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.											
		Da cheng 2013.05.28	Da cheng 2013.05.28		<table><tr><th colspan="2">Tolerance</th></tr><tr><td>X.</td><td>±0.50</td></tr><tr><td>X.X</td><td>±0.30</td></tr><tr><td>X.XX</td><td>±0.10</td></tr><tr><td>X°</td><td>±1°</td></tr></table>	Tolerance		X.	±0.50	X.X	±0.30	X.XX	±0.10	X°	±1°
Tolerance															
X.	±0.50														
X.X	±0.30														
X.XX	±0.10														
X°	±1°														
				SHEET: 01/01	REV.: F										