



RoHS Compliant

REV	SIGN	DATE	DESCRIPTION	APPROVER
A		2024.10.09	Initial Release	Shao Bo
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				






Material:

- Item ① Terminal Body: PA6,
- Item ② Terminal lever: PA6 ,
- Item ③ Terminal Contact: Copper alloy,
- Item ④ Spring: Stainless

Electrical:

TUV (IEC60998-2-2)



- Voltage rating: 450V
- Current rating: 17.5A
- Wire range: 0.75-2.5mm²
- Wire strip length: 8-10 mm
- Withstanding Voltage: 2.5KV AC
- Insulation Resistance: DV500V 500MΩ min
- Operating temperature: -20°C to +85°C
- Assembling temperature: -5°C to +85°C
- Safety Approval:
- Critical dimension:



Part No. AQT 5 10 N H N 9 x x G

RoHS compliant
(lead<4%)
In copper Alloy

00: "@" Logo (Standard)
0A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.



Recommended PCB layout
Top View

Amphenol ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		AQT series Quick wiring terminal block,5P, without button, with hook					
PART NO.		AQT510NHN9xxG		DWG NO.	8AQT0015		
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
		Shao Bo 2024.10.09			UNIT: mm		X. ±0.50
					SCALE: 1:1		X.X ±0.30
					SHEET: 01/01		X.XX ±0.10
				REV.: A0		X° ±1°	