






RoHS Compliant



SECTION A-A



PCB Layout

Rev.	SIGN	DATE	DESCRIPTION	APPROVER
B	—	2010.11.09		Runner
C	△	2024.12.04	Update the drawing	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Materials

- Item③ Terminal body:NL66 (UL 94V-0)
- Item⑤ Terminal screw: Steel Zinc plating “-” slot type
- Item⑦ Clamp: Brass . Ni plated
- Item① Long wire guard solder pin: Brass .Tin plated
- Item⑥ Center wire guard solder pin: Brass .Tin plated
- Item② Short Wire guard solder pin: Brass .Tin plated

Electrical

- Voltage rating: 600VAC
- Current rating: 20A
- Wire range:
- Solid wire(AWG): 12-30
- Stranded wire(AWG): 12-30
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 2.2KV
- Operating temperature: -40°C to +115°C
- Wave Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- Critical dimension: ▲

K7 03 0 3 x 1 xxxx G

COLOR

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- 9 White(RAL1102)
- C Green(RAL6018/U)

G: RoHS compliant
(lead<4%) In copper Alloy

0000: “@” Logo (Standard)
000A: “ANYTEK” Mark

Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY
FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE
PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		K7 7.5 SERIES 3P (Left)				
PART NO.	K70303x1xxxxG			DWG NO.	8K70002	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Guoxue 2024.12.04	Guoxue 2024.12.04		UNIT: mm	X. ±0.5
					SCALE: NONE	X.X ±0.3
						X.XX ±0.1
					SHEET: 01/01	REV.: C