





RoHS Compliant


SIGN	DATE	DESCRIPTION	APPROVER
B	2019.11.07	The first release	Guoxue
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			



N=NUMBER OF CONTACTS

DIM		TOL		
		2x2P--2x6P	2x7P--2x12P	2x13P--2x16P
Dim A	$(N/2-1) \times 3.5 + 14.4$	± 0.15	± 0.20	± 0.25
Dim B	$(N/2-1) \times 3.5$			
Dim P	$(N/2-1) \times 3.5$			

Fill the glue



SECTION Q-Q

Material:

- Item ① Terminal(housing): High temp. polyamide (UL94 V-0)
- Item ② Contact pin : Copper Tin plated
- Item ③ Flange screw NUT: Brass M 2.5

Electrical:

- Voltage rating: 160V
- Current rating: 5.5A
- Withstanding Voltage: 1.32 KV
- Operating temperature: -40°C to $+110^{\circ}\text{C}$
- Reflow Soldering temperature: $260^{\circ}\text{C}/10$ Sec. Max.
- APPROVAL: 
- Critical dimension: 

cULus

KE xx 1 B x 0 xxxx G

No. OF POLES
04: 2x2 POLES
06: 2x3 POLES
:
32: 2x16 POLES
COLOR
0: BLACK

RoHS compliant
(lead<4%)
In copper Alloy

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

**Amphenol
ANYTEK****CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KE 3.5mm With Flange Series (Vertical) THR type						
PART NO.		KExx1Bx0xxxxG			DWG NO.		8KE0429	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
			Guoxue 2019.11.07	Guoxue 2019.11.07		UNIT: mm		X. ±0.50
						SCALE: NONE		X.X ±0.30
						SHEET: 01/01		X.XX ±0.10
					REV: B		X° ±1°	