




RoHS Compliant

REV	SIGN	DATE	DESCRIPTION	APPROVER
A2		2025.08.15	Initial Release	Shao Bo
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

- Material:
- Item ① Terminal upper body: Thermoplastic (UL94V-0),
 - Item ② Terminal bottom body: Thermoplastic (UL94V-0),
 - Item ③ Terminal lever: Thermoplastic
 - Item ④ Terminal Contact: High conductive copper alloy
 - Item ⑤ Spring: Stainless,

- Electrical: UL1059 Group B
- Voltage rating: 300 V
 - Current rating: 20A
 - Wire range:
Solid wire: 24-12AWG
Stranded wire: 24-12AWG
 - Wire strip length: 11 mm
 - Operating temperature: -40°C to +105°C
 - Assembling temperature: -5°C to +105°C
 - Safety Approval:

Part No. **PL xx 5 x x H H xxxx G**

NO. OF POLES

02: 2 POLES

03: 3 POLES

... ..

16: 16 POLES

Body color

0 Black

1 natural color

2. Red

3. Orange

4. Yellow

5 Green (RAL6018/T)

6 Blue

8 Grey (標準色)

9 White

C: Green (RAL 6018/U)

Lever color

0 Black

1 natural color

2. Red

3. Orange

4. Yellow

5 Green (RAL6018/T)

6 Blue

8 Grey (標準色)

9 White

C: Green (RAL 6018/U)

RoHS compliant (lead<4%) In copper Alloy

00x0: “@” Logo (Standard)

Any special item by customer request. please contact sales department.

Amphenol
ANYTEK

CUSTOMER COPY
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		PL 5.08 series 2P-16P terminal block, 180° wire insertion, with hook				
PART NO.	PLxx5xxHHxxxxG			DWG NO.	8PL0003	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
Roy 2025.12.02	Roy 2025.12.02	Shao Bo 2025.08.15	Shao Bo 2025.08.15		UNIT: mm	X. ±0.50
					SCALE: 2:1	X.X ±0.30
					REV.: A2	X.XX ±0.10
				SHEET: 01/01	X° ±1°	