

E



Technical drawing of a 4-core cable. The drawing shows a cross-section of the cable with four conductors. Each conductor has a diameter of 5.08 mm. The conductors are arranged in a square pattern. The drawing also shows the outer jacket and the internal insulation of the conductors.

Material:

- Item (a) Terminal upper body: Thermoplastic (UL94V-0),
- Item (b) Terminal bottom body: Thermoplastic (UL94V-0),
- Item (c) Terminal lever: Thermoplastic
- Item (d) Terminal Contact: High conductive copper alloy
- Item (e) Spring: Stainless,

Electrical: UL1059 Group B

- Voltage rating: 300 V
- Current rating: 20A
- Wire range:
  - Solid wire: 24-12AWG
  - Stranded wire: 24-12AWG
- Wire strip length: 11 mm
- Operating temperature: -40°C to +105°C
- Assembling temperature: -5°C to +105°C
- Safety Approval:

NO. OF POLES  
02: 2 POLES  
03: 3 POLES  
... ..  
16: 16 POLES

- Body color
- 0 Black
  - 1 natural color
  - 2. Red
  - 3. Orange
  - 4. Yellow
  - 5 Green (RAL6018/T)
  - 6 Blue
  - 8 Grey (標準色)
  - 9 White
- C: Green  
(RAL 6018/U)

- Lever color
- 0 Black
- 1 natural color
2. Red
3. Orange
4. Yellow
- 5 Green (RAL6018/T)
- 6 Blue
- 8 Grey (標準色)
- 9 White
- C: Green  
(RAL 6018/U)

RoHS compliant  
(lead<4%)  
In copper Alloy

- 00x0: "@ " Logo (Standard)  
Any special item by  
customer request.  
please contact sales  
department.

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

A