





RoHS Compliant

REV	SIGN	DATE	DESCRIPTION	APPROVER
A0		2021.03.08	Initial Release	LENA
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				



Part No. AMI SH 2 24 F I F 00G

Insulation System:
F : Class F
Contact Material:
I : AgSnO₂+In(new)
Type:
F : New Structure DC Coil
Coil Voltage:
24: 24V(VDC)
Number of pole,
2: Two Poles
Type of sealing :
SH:RT III wash tight
TYPE : AMI

COIL SPECIFICATION

- Coil Nominal Voltage: 24V DC
- Coil Nominal Current: 16.7mA
- Coil Resistance: 1,440Ω ±10%
- Coil Power Consumption: Abt. 0.40W
- Pull-In Voltage(VDC): 19.2V Max
- Drop-Out Voltage(VDC): 1.2V Min
- Maximum Allowable Voltage: 31.2V
- Operate Time: 12 mSec. Max.
- Release Time: 8 mSec. Max.

CONTACT RATING

- Rated Load(Resistive): 8A 250V AC / 8A 30V DC
- Rated Carrying Current: 8A
- Max. Allowable Voltage: AC 250V / DC 300V
- Max. Allowable Current: 8A
- Max. Allowable Power Force: 2000VA 240W
- Contact Material: Ag Alloy
- Contact Form: DPDT

ELECTRICAL

- Dielectric Strength:
 - Between Coil & Contact: 5,000V AC (50/60 Hz for 1 minute)
 - Between Contact: 1,000V AC (50/60 Hz for 1 minute)
- Contact Resistance: 100mΩ Max. at 1A, 6V DC
- Insulation Resistance: 100MΩ Min at 500V DC

MECHANICAL

- Life Expectancy(Operations):
 - Electrical: 1 x 10⁵ operations at Rated Resistive load
 - Mechanical: 1 x 10⁷ operations at No Resistive load
- Operating Temperature: -40°C ~ 105°C
- Safety Approval: UL

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		AMI Series Relay, RT III Wash Tight, 24V DC						
PART NO.		AMISH224FIF00G			DWG NO.		8AMI0003	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
			LENA 2021.03.08	LENA 2021.03.08			UNIT: mm	X. ±0.50
							SCALE: 2:1	X.X ±0.30
					SHEET: 01/01		REV.: A0	X.XX ±0.10
								X° ±1°