

REV	SIGN	DATE	DESCRIPTION	APPROVER
C		10/14/09	The dimension changed from 3.91to3.70	Kind
		10/14/09	The dimension changed from 3.20to3.30+0.20/-0	Kind
D		05/15/14	The dimension changed from 3.30+0.05/-0.05 to 3.50+0.10/-0.10	Chen Bo
E		01/11/16	Delete the dimension 78" & change the left view to right view	Evan
		01/11/16	Change the dimension from 0.30 to 0.30 ^{+0.05} _{-0.10}	Evan
		01/11/16	Change the dimension from 15.04 to 14.05 ^{+0.32} ₋₀	Evan
		01/11/16	Change the dimension from 3.00 to 3.0	Evan
		01/11/16	Change the dimension from 24.55 to 25.0	Evan
		01/11/16	Change the dimension from 3.70±0.05 to 3.70 ^{+0.05} _{-0.15}	Evan
F		06/16-25	update the drawing	Chen Bo
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

NOTE:

1.MATERIAL:

- Item④ Wire guard:PHBZ(T=0.3mm),Tin plated.
- Item⑤ Spring : Stainless steel(T=0.15mm)
- Male contact is inserted into the plug housing KI 3.81 after crimping the conductor, for conductors from 0.5 to 1.0 mm²
- Critical dimension: ▲ ,Other sizes are reference sizes

Amphenol ANYTEK				CUSTOMER COPY ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE		AO 3.81 腳子彈片成品 (wire range 0.5~1.0mm ²)					
PART NO.		AO00000000000G		DWG NO.		8A00001	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Chen Bo 06/16-25	Chen Bo 05/15 '14			UNIT: mm
							SCALE: NONE
					SHEET: 01/01		REV: F
						X.X ±0.30	
						X.XX ±0.10	
						X° ±1°	