






RoHS Compliant

REV	SIGN	DATE	DESCRIPTION	APPROVER
A0		2021.03.08	Initial Release	LENA
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				



P.C.B. LAYOUT
Bottom View

Part No. AKE 1 12 D M N 00G

Contact Material
N : AgSnO₂
Contact Form
M : One Form A
Coil Type
D : Standard DC Coil
Coil Voltage:
24: 24V(VDC)
Number of pole,
1: One Pole
TYPE : AKE

COIL SPECIFICATION

- Coil Nominal Voltage: 12V DC
- Coil Nominal Current: 16.7mA
- Coil Resistance: 720Ω ±10%
- Coil Power Consumption: Abt. 0.2W
- Pull-In Voltage(VDC): 9V Max
- Drop-Out Voltage(VDC): 0.6V Min
- Maximum Allowable Voltage: 18V
- Operate Time: 8 mSec. Max.
- Release Time: 6 mSec. Max.

CONTACT RATING

- Rated Load(Resistive): 8A 250V AC / 8A 30V DC
- Max. Allowable Voltage: AC 440V / DC 30V
- Max. Allowable Current: 8A
- Max. Allowable Power Force: 2000VA 240W
- Contact Material: Ag Alloy
- Contact Form: SPST

ELECTRICAL

- Dielectric Strength:
 - Between Coil & Contact: 4,000V AC (50/60 Hz for 1 minute)
 - Between Contact: 1,000V AC (50/60 Hz for 1 minute)
- Contact Resistance: 100mΩ Max. at 1A, 6V DC
- Insulation Resistance: 100MΩ Min at 500V DC

MECHANICAL

- Life Expectancy(Operations):
 - Electrical: 1 x 10⁶ operations at Rated Resistive load
 - Mechanical: 1 x 10⁷ operations at No Resistive load
- Operating Temperature: -40°C ~ 85°C
- Safety Approval: UL

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	AKE Series Relay, one pole, 12V DC,							
PART NO.	AKE112DMN00G			DWG NO.	8AKE0009			
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance	
		LENA 2021.03.08	LENA 2021.03.08		UNIT: mm	X.	±0.50	
					SCALE: 2:1	X.X	±0.30	
					REV: A0	X.XX	±0.10	
				SHEET: 01/01				
							X° ±1°	