




RoHS Compliant



SECTION A-A



KX xx C 1 x 0 xxxx G

No. OF POLES
02: 2 POLES
03: 3 POLES
10: 10 POLES

COLOR
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

G RoHS compliant (lead<4%)
In copper Alloy

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request.
please contact sales department.

POLE	2	3	4	5	6	7	8	9	10
Dim.L	31.3	46.3	61.3	76.3	91.3	106.3	121.3	136.3	151.3
Dim.P	15.0	30.0	45.0	60.0	75.0	90.0	105.0	120.0	135.0
Tol.	±0.20			±0.35			±0.50		

REV	SIGN	DATE	DESCRIPTION	APPROVER
B		05/03-11	Initial release	Runner
C	△	05/13-20	Add RoHS Compliant, and Amphenol Logo	Chen Bo
	△	05/13-20	Change the symbol of critical dimension	Chen Bo
	△	05/13-20	add cULus safety certification mark	Chen Bo
	△	05/13-20	add the colour code, change the torque force	Chen Bo
	△	05/13-20	update the dimensional	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ① Terminal housing: Thermoplastic (UL94V-0)
- Item ② Terminal cover: Thermoplastic (UL94V-0)
- Item ③ Female contact: Copper. Tin plated
- Item ④ Wire guard: Stainless Steel
- Item ⑤ Clamp: Steel Stamping, Zinc plated
- Item ⑥ Terminal screw: Zinc plating"-slot type, M5

Electrical: cULus

- Voltage rating: 600 V
- Current rating: 115 A
- Wire range:
- Solid wire(AWG): 2-20
- Stranded wire(AWG): 2-20
- Torque(Lb-In): 31.5 (The maximum allowable torque is 36.5Lb-In)
- Screw: M5
- Wire strip length: 19-20mm
- Withstanding Voltage: 2.2 KV
- Operating temperature: -40°C to +115°C
- ③ APPROVAL: cULus
- ② Critical dimension: ▲

**Amphenol**
ANYTEK**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KX 15.0mm Series (without flange) 2P-10P							
PART NO.		KXxxC1x0xxxxG			DWG NO.		8KX0006		
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
		Chen Bo 05/13-20	Chen Bo 05/13-20		UNIT: mm		X. ±0.50		
					SCALE: NONE		X.X ±0.30		
							X.XX ±0.10		
					SHEET: 01/01		REV: C		X° ±1°