


RoHS Compliant




Solid Block
02 2 CONTACTS
03 3 CONTACTS
... ..
24 24 CONTACTS

TJ xx 31x 2 xxxx G


0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)

G RoHS compliant
(lead<4%)
In copper Alloy
0000: "@" Logo
000A: "ANYTEK" Mark
0091: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.



Dim.L = N x 3.81
Dim.B = (N-1) x 3.81
Dim.C = N x 3.81+10.08
Dim.D = (N-1) x 3.81+9.0
N= number of poles

poles Dim. Tolerance	2P-6P	7P-12P	13P-18P	19P-24P
Dim.L	±0.15	±0.20	±0.25	±0.30
Dim.B	±0.10	±0.15	±0.20	±0.25
Dim.C	±0.15	±0.20	±0.25	±0.30
Dim.D	±0.15	±0.20	±0.25	±0.30



REV	SIGN	DATE	DESCRIPTION	APPROVER
C	△	11/01'05	Electrical standard changed.	Marvin
D	△	04/20'06	2p to 6p with wedge is changed.	Marvin
E	△	06/06'06	2p to 6p with wedge is removed	Marvin
F	△	8/13'06	Added VDE standard	梁仁松
G	△	12/15'08	Flange screw changed from "-" slot type to "+/-" slot type	Kind
H	△	2010.07.12	The solid and Stranded wire are changed from 16-26 to 16-28	Chen Bo
I	△	2010.07.12	Rmove the CSA mark	Chen Bo
J	△	08/23-18	update the drawing, Add RoHS compliant, Replace the drawing frame	zhangcan
J	△	08/23-18	Material: Change a to @, Item @ Female contact: PhBz, Bright Tin plated over Nickel plated.	zhangcan
J	△	08/23-18	all Critical dimension Change △ to ▲, add ● Critical dimension: ▲	zhangcan
J	△	08/23-18	add Dim.C = N x 3.81+10.4, Dim.D = (N-1) x 3.81+9.0, add Dim.C, Dim.D Tolerance.	zhangcan
J	△	08/23-18	The solid and Stranded wire are changed from 16-26 / 16-28 to 16-28	zhangcan
J	△	08/23-18	change G RoHS compliant (lead<4%) In copper Alloy	zhangcan
K	△	11/26-18	Change the dimension from 5.2 to 5.04	Chen Bo
L	△	09/24-24	update the drawing	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item (a) Clamp: Brass (CuZn) Ni plated
- Item (b) Terminal screw: Steel Zinc plating "-" slot type
- Item (c) Female contact: PhBz, Bright Tin plated over Nickel plated
- Item (d) Terminal (housing): Thermoplastic (UL94V-0)
- Item (e) Terminal (cover): Thermoplastic (UL94V-0)
- Item (f) With flange screw: steel M2.5 Zinc plating "+/-" slot type

Electrical cULus/VDE

- Voltage rating: 300VAC/300VAC
- Current rating: 10A/10.5A
- Wire range: 1.5mm²
- Solid wire (AWG): 16-28
- Stranded wire (AWG): 16-28
- Torque: 3Lb-In/0.2Nm
- Screw: M2
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus VDE
- Critical dimension: ▲

**Amphenol
ANYTEK**

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TJ-3.81mm Series With flange			
PART NO.	TJxx31x2xxxxG			DWG NO.	8TJ0602
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Chen Bo 09/23-24	Chen Bo 11/26-18		Tolerance
					X. ±0.50
					X.X ±0.30
				SHEET: 01/01	X.XX ±0.10
				REV.: L	X° ±1°