




RoHS Compliant




P.C.B LAYOUT
TOP VIEW

N = Number of poles

Dim A=N×5.0+2.5

Dim B=(N-1)×5.0

Pole	Dim A
1P	±0.15
2-6p	±0.20
7-12p	±0.25
13-18p	±0.35
19-24p	±0.40



REV	SIGN	DATE	DESCRIPTION	APPROVER
D	△	11.01'05	Standard spec is changed.	Marivn
E	△	02/01'07	Soldering temperature is changed from 245°C to 250°C	Marivn
E1	△	03/29'10	The wire inlet is changed.	Tason
F	△	10/22'13	Update the drawing	Guoxue
G	△	2018.04.18	Through TUV certification and Update the drawing	Zia
H	△	2018.07.10	Add two cylinder	Chen Bo
I	△	2025.06.16	Add the color	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material ● Item ① Terminal body(metal housing): steel, stamped Zinc plated.

● Item ② Terminal screw: Steel, Zinc plated “-” slot type

● Item ③ Contacts: Brass, Tin plated

● Item ④ Firm wire chunk: steel, Zinc plated

● Item ⑤ Insulator (housing): NL66 (UL94V-0)

● Item ⑥ Insulator (housing): NL66 (UL94V-0)

△ △ Electrical cULus TUV

● Voltage rating: 300V

300V

● Current rating: 20A

32A

● Wire range:

0.34-4.0mm²

● Solid wire(AWG): 12-22

● Stranded wire(AWG): 12-22

● Torque(Lb-In): 2.4

● Screw: M2.5

● Wire strip length: 10-11mm

● Withstanding Voltage: 1.6KV 2.5KV

△ ● Operating temperature: -40°C to +115°C

△ △ ● Wave soldering temperature: 260°C±5°C/5 Sec

△ △ ● Safety Approval: cULus TUV

● Critical dimension:

● Reference dimension: (×) The dimensions of pitch are just for reference, take the actual assembly result as a judgment when inserting the terminal block into the PCB hole.

TR xx 05 x 1 xxxx G

		COLOR		
01 1Pole	0 Black (RAL9005)	0000: “@” Logo	G RoHS compliant	
02 2Poles	2 Red (RAL3001/D)	000A: “ANYTEK” Logo	(lead<4%)	
... ..	3 Orange(RAL2011/P)	Any special item by	In copper Alloy	
24 24Poles	4 Yellow(RAL1018/A)	customer request.		
	5 Green(RAL6018/T)	please contact sales		
	6 Blue (RAL5015/A)	department.		
	8 Grey(RAL7035/D)			
	△ 9 White(RAL1102)			
	C Green(RAL 6018/U)			

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	TR 5.0 Series Horizontal (180D wire inlet)				
PART NO.	TRxx05x1xxxxG			DWG NO.	8TR0001
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Guoxue 2025.06.16	Guoxue 2025.06.16		Tolerance
				UNIT: mm	X. ±0.50
				SCALE: NONE	X.X ±0.30
				SHEET: 01/01	X.XX ±0.10
				REV.: I	X° ±1°